

## Parker- kulové uzavírací ventily Bi-flow

### Technické údaje

Typ	Schiessl	Připojení Ø mm	Délka mm
LWM6	241.2801	6 let.	117
LWM8	241.2802	8 let.	118,5
LWM10	241.2803	10 let.	124,5
LWM12	241.2804	12 let.	131,5
LWM15	241.2805	15 let.	145
LWM16	241.2806	16 let.	143
LWM18	241.2807	18 let.	143
LWM22	241.2808	22 let.	198,5
LWM28	241.2809	28 let.	205
LWM35	241.2810	35 let.	220
LWM42	241.2811	42 let.	242
LWM54	241.2812	54 let.	273
LWM64	241.2813	64 let.	283



*Danfoss*

## Danfoss- vysokotlaká průhledítka SGP

### Technické údaje

Typ	Schiessl	Danfoss	Připojení
SGN+6	252.0442	014F0161	7/16"
SGN+10	252.0443	014F0162	5/8"
SGN+12	252.0444	014F0163	3/4"
SGN+16	252.0445	014F0165	7/8"
SGN+6s	252.0450	014F0191	6mm let.
SGN+10s	252.0451	014F0192	10mm let.
SGN+12S	252.0452	014F0193	12mm let.
SGN+16s	252.0453	014F0184	16mm let.
SGN+18s	252.0454	014F0195	18mm let.
SGN+22s	252.0455	014F0186	22mm let.

**Poznámka:** Maximální pracovní přetlak 52 bar i pro R410A, R744(CO<sub>2</sub>)



## Honeywell - průhledítka SLI

### Technické údaje

Schiessl	Typ	Připojení
252.1011	SLI 6	6mm let.
252.1012	SLI 10	10mm let.
252.1013	SLI 12	12mm let.
252.1015	SLI 16	16mm let.
252.1016	SLI 18	18mm let.
252.1017	SLI 22	22mm let.

**Poznámka:** Maximální povolený tlak 40 bar, teplota +80°C

**Honeywell**

